



PRODUCT RANGE

AIR HANDLING UNITS



AZ

Air-handling units with panel thickness 25, 50, 100 mm or 45mm with thermal cut. Combinable modular structure. Customised executions on request.



ZAE

Air-handling units with 60mm panel thickness with thermal cut. Performances certified according to Eurovent norms.



AZS

Air-handling units with internal invisible frame and 50 or 100mm panels. Exclusive joints between the panels and The frame for total thermal cut.



AZH

Air-handling units with internal invisible frame in stainless steel and 50 or 100mm panels also in stainless steel for hospital and food industry applications.



AZV

Air-handling units with 60mm glass-resin panels specifically designed for food industry clean rooms applications.



AZ-I, AZS I, ZAE I

Air-handling units complete with power and control control board with microprocessor for 'plug & play' supply.



HEAT RECOVERY UNITS



URE

Aluminium frame and 20 mm panels
Air volumes from 290 to 4000 m³/h
Efficiency 50-55%.



URP

Aluminium frame and 25mm panels
Air volumes from 1500 to 5500 m³/h
Efficiency 60-65% with by-pass



URPX


Aluminium frame and 25mm panels.
Air volumes from 1000 to 5000 m³/h.
Efficiency 90-95% with option for by-pass.



URE-I, URP-I, URPX-I


Heat recovery units complete with power and control board, 'plug & play'.

AIR EXHAUST UNITS



CV

Air exhaust units from 500 to 38000 m³/h.
Aluminium frame and 25mm panels.



CVM

Air exhaust units from 300 to 4500 m³/h.
Aluminium frame and 25mm panels.



EV

Air exhaust units from 400 to 4300 m³/h.
Self-supporting panels. Low-profile units.



AIR CONDITIONING UNITS



PA

Self-supporting panels. Low-profile units.
Air volumes from 930 to 4350 m³/h.



TS

Aluminium frame and 25mm panels.
Air volumes from 700 to 4000 m³/h.



TA

Aluminium frame and 25mm panels.
Air volumes from 600 to 7000 m³/h with
self-adjusting fans.



T

Aluminium frame and 25mm panels.
Air volumes from 1.500 to 30.000 m³/h.



TS low profile

Aluminium frame and 25mm panels. Height 450mm.
Air volumes from 1300 to 3500 m³/h with self-adjusting fans.
Possibility to install a complete 'plug&play' control board.

T.C.F.

Termoventilatori Condizionatori Felsinea S.r.l.

Via Giuseppe di Vittorio 5

40057 Cadriano di Granarolo Emilia (BO)

www.tcf.it

TCF, the air the way you want it